

# PRODUCT DATA SHEET

## Product Description

Ultracurve 550LSE is a 6.0mil flexible clear polymeric vinyl film, backed with a highly aggressive pressure sensitive acrylic adhesive system, specifically engineered to adhere to difficult substrates, while removing cleanly. Suggested application to low surface energy plastics, powdercoated metals, and most smooth and textured metal surfaces.

## Recommended End Uses

Substance Incorporated recommends the following end uses for Ultracurve 550LSE:

- Transparent fender/swingarm decals for Motocross Bikes and ATUs.
- Suspension decals requiring excellent adhesion with clean removability.
- Industrial applications to polypropylene requiring high heat-resistance.
- Permanent adhesion to smooth and lightly textured plastics and metals.

## Performance Characteristics

Characteristic	Typical Value
Material	4.0 mil Polymeric Calendered Vinyl
Color	Clear
Tensile Strength	15.2 pounds/inch
Adhesive	Clear Solvent-Based Pressure Sensitive Acrylic
Adhesive Thickness	2.0 mil (0.056mm) +/- 10%
Peel Adhesion	6.0 pounds/inch from Stainless Steel
Liner	90LB Natural Brown PE Coated Layflat Paper
Liner Release	32 grams/inch
Dimensional Stability	0.031 inch (0.8 mm)
Application Temp.	32°F to 80°F recommended, test prior to specific application
Temperature Range	-65°F to 220°F
Shelf Life	2 years when stored at 70°F and 50% relative humidity
Print Compatibility	Solvent, Eco-Solvent, Latex, UV, and Thermal Transfer Inks
Graphic Life	Outdoor durability up to 7 years (unprinted), permanent
Chemical Resistance	Resists mild acids, mild alkalis, solvents, and salts. Excellent resistance to water, including immersion.

## Installation Recommendations

Before applying an overlamine, allow 24 hours for print to dry. Application surface must be free of dust, dirt, debris, grease, and other contaminants. We highly recommend cleaning the installation surface with isopropyl alcohol prior to application. Dry installation is recommended. Please test any application fluid prior to use. Mild heat may be used during installation to help 550LSE conform to irregular surfaces.

### Disclaimer

All descriptive information presented within this Product Data Sheet is intended for reference purposes only. This information does not suggest or constitute a verbal or written warranty of any kind. The end user shall be responsible for independently testing the suitability of their application, prior to final use. The liability of Substance Incorporated will not exceed the purchase price of materials.